

Applications

Airline oils are high guality oils with a naturally high

MANUTEC AIRLINE M 22

Product Code: COMP001 Revision: 20220323	 viscosity index, it is ideal for the lubrication of pneumatic tools, valves and related equipment. It has a low pour point and special additives to protect against rust, corrosion, water washing and resistance to foaming. Intended for use in systems where it may be necessary to draw off any 	
	separated water and to ensure the quick creation of mist for the lubrication of downstream pneumatic equipment.	
	Recommended by Aztec Oils as suitable for the following applications	
High Performance Industrial Libricant	 Airline Oils are recommended for use in air tools of most types including road drills, jack hammers, air speed saws and torque wrenches. It is also recommended for air motors and the lubrication of pneumatic rams and cylinders. In addition, Airline Oils can be used for general lubrication in industrial applications. 	
Mineral based airline lubricant.	Benefits	
Available Pack Sizes	 Demulsifying to ensure rapid water separation. Excellent anti-wear characteristics. Good anti-foam and air release properties. Outstanding corrosion protection. Superior oxidation resistance to provide a long service life. 	
Typical ⁻	Test Data	
Appearance	Straw/light amber liquid	
Density @ 15°C (kg/m3)	ASTM D4052 0.85	

Density @ 15°C (kg/m3)	ASTM D4052	0.85
Flash Point (°C)	ASTM D92	>130
Kinematic Viscosity @ 40°C (mm/s ²)	ASTM D445	22
Kinematic Viscosity @ 100°C (mm/s ²)	ASTM D445	4.3
Pour Point (°C)	ASTM D97	<-10
Viscosity Index	ASTM D2207	95

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at www.aztecoils.co.uk.
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

In line with our policy of continued improvement, Aztec Oils reserve the right to change specifications and availability without prior notice. This product, used according to our recommendations and for its designed application, does not represent any particular risk. The information present in this technical data sheet is indicative of the product and is given in good faith, but should not form part of any specification.