



**BLT**

# Turnbuckles Jaw & Jaw

drop forged



<b>Material</b>	Drop forged high tensile steel SAE 1035 or 1045
<b>Safety Factor</b>	MBL equals 5 x WLL
<b>Standard</b>	Generally to ASTM F1145-92 Formerly US Fed Spec FF-T-791b
<b>Finish</b>	Hot dipped galvanised
<b>Certification</b>	As standard; EC Declaration of Conformity

WLL	Diameter	Take	Length	Length	Opening	Length	Diameter	Thickness	Diameter	Product	Weight
t	a	Up	Position	Position	Jaw	Inside	Pin	Jaw Eye	Jaw Eye	Code	Each
inch	inch	inch	mm	mm	mm	mm	mm	mm	mm		kg
0.54	3/8	6	302	454	13	22	8	8	21	61101	0.37
1.00	1/2	6	338	490	16	26	9.5	10	25	61102	0.73
1.00	1/2	9	414	642	16	26	9.5	10	25	61103	0.79
1.00	1/2	12	490	795	16	26	9.5	10	25	61104	0.96
1.59	5/8	6	394	546	18	33	13	13	33	61105	1.37
1.59	5/8	9	470	698	18	33	13	13	33	61106	1.41
1.59	5/8	12	546	851	18	33	13	13	33	61107	1.53
1.59	5/8	18	701	1150	18	33	13	13	33	61108	1.86
2.36	3/4	6	432	584	23	38	15.5	16	41	61109	1.86
2.36	3/4	9	508	736	23	38	15.5	16	41	61110	2.31
2.36	3/4	12	584	889	23	38	15.5	16	41	61111	2.56
2.36	3/4	18	737	1194	23	38	15.5	16	41	61112	3.11
3.27	7/8	12	625	854	27	44	19	18	48	61113	3.71
3.27	7/8	18	778	1121	27	44	19	18	48	61114	4.14
4.54	1	6	524	676	30	52	22	20	54	61115	4.29
4.54	1	12	676	981	30	52	22	20	54	61116	5.07
4.54	1	18	829	1286	30	52	22	20	54	61117	6.62
4.54	1	24	980	1592	30	52	22	20	54	61118	7.85
6.90	1.1/4	12	760	1055	44	73	29	25	67	61119	9.48
6.90	1.1/4	18	912	1370	44	73	29	25	67	61120	11.60
6.90	1.1/4	24	1064	1665	44	73	29	25	67	61121	13.00
9.71	1.1/2	12	823	1129	52	70	35	27	80	61122	13.60
9.71	1.1/2	18	975	1434	52	70	35	27	80	61123	14.30
9.71	1.1/2	24	1228	1738	52	70	35	27	80	61124	18.40
12.70	1.3/4	18	1060	1533	59	85	41	33	90	61125	25.00
12.70	1.3/4	24	1213	1838	59	85	41	33	90	61126	28.70
16.78	2	24	1315	2011	64	93	41	39	108	61127	45.40
27.22	2.1/2	24	1486	2098	75	114	57	38	143	61128	73.00
34.02	2.3/4	24	1562	2171	89	110	70	42	156	61129	98.00